## Listing of Claims:

- (Previously Presented) A device adapted to be used with tissue, comprising: an endoscope having a distal end; and
  - a clip, the clip coupled to the endoscope, the clip comprising:
    - a ring portion sized to fit on the distal end of the endoscope;
- a plurality of legs attached to the ring portion, each of the legs being movable between an open position and a closed position to compress tissue without a substantial change in configuration of the ring portion; and
- a locking mechanism to restrict movement of each of the legs from the closed to the open position.
- (Previously Presented) A device adapted to be used with tissue, comprising: an endoscope having a distal end; and
  - a clip, the clip coupled to the endoscope, the clip comprising:
- a plurality of legs attached to a ring portion, each of the legs being movable between an open position and a closed position to compress the tissue; and
- a locking mechanism to restrict movement of each of the legs from the closed to the open position,
  - wherein the locking mechanism is a ratchet mechanism.
- (Original) The device according to claim 2, wherein the ratchet mechanism comprises a plurality of snaps formed on one of the legs and the ring portion.
- (Previously Presented) The device according to claim 1, wherein the locking mechanism
  is in physical communication with the ring portion at least when the legs are in an open position.
- (Previously Presented) The device according to claim 1, further comprising a hinge connecting the ring portion to each of the legs.

- (Previously Presented) The device according to claim 5, wherein the hinge is a pin and slot hinge, the pin extending from one of the ring portion and each of the legs.
- (Previously Presented) A device adapted to be used with tissue, comprising: an endoscone having a distal end; and
  - a clip, the clip coupled to the endoscope, the clip comprising:
    - a ring portion.
- a plurality of legs attached to the ring portion, each of the legs being movable between an open position and a closed position to compress the tissue;
- a locking mechanism to restrict movement of each of the legs from the closed to the open position; and
  - a catch to mechanically retain the legs in the open position.
- (Previously Presented) The device according to claim 5, wherein the hinge is a four bar mechanism.
- (Original) The device according to claim 1, further comprising resilient devices adapted to urge the legs in one of the open and closed positions.
- (Currently Amended) A device adapted to be used with tissue, comprising: an endoscope having a distal end; and
  - a clip, the clip coupled to the endoscope, the clip comprising:
    - a ring portion,
- a plurality of legs attached to the ring portion, each of the legs being movable between an open position and a closed position to compress the tissue;
- a locking mechanism to restrict movement of each of the legs from the closed to the open position; and
- an actuator mechanism to move each of the legs from the open to the closed position;

wherein the actuator mechanism comprises strings pulling each of the legs in the closed position.

## (Canceled)

- (Previously Presented) The device according to claim 1, further comprising an actuator mechanism including a rack and pinion arrangement.
- (Previously Presented) The device according to claim 1, further comprising an actuator mechanism including a hydraulic piston exerting a force on each of the legs.
- 14. (Previously Presented) The device according to claim 1, further comprising an actuator mechanism including a remotely operated sheath moving each of the legs to the closed position.
- (Previously Presented) A device adapted to be used with tissue, comprising: an endoscope having a distal end; and
  - a clip, the clip coupled to the endoscope, the clip comprising:
    - a ring,
- a plurality of legs attached to the ring, each of the legs being movable between an open position and a closed position to compress the tissue;
- a locking mechanism to restrict movement of each of the legs from the closed to the open position; and
  - a releasable attachment connecting the ring to the endoscope.
- (Previously Presented) The device according to claim 15, wherein the releasable attachment comprises a thread forming a stitch between the ring and the endoscope.
- 17. (Previously Presented) The device according to claim 15, wherein the releasable attachment comprises a seal connecting the ring to the endoscope, and a thread embedded in the seal, such that removal of the thread cuts the seal.

- 18. (Previously Presented) The device according to claim 15, wherein the releasable attachment comprises a protrusion extending from one of the ring and the endoscope and a complementary groove formed in the other of the ring and the endoscope, wherein the protrusion and the groove are connected frictionally.
- 19. (Previously Presented) The device according to claim 15, wherein the releasable attachment comprises a catch extending from one of the ring and the endoscope, a complementary slot formed in the other of the ring and the endoscope, and an actuator for releasing the catch from the groove to release the ring.
- (Previously Presented) The device according to claim 1, wherein the plurality of legs are releasably attached to the ring.